## **MODEL: ROHINI-1**

## **Harness:**

Anchor point: One dorsal D-ring for fall arrest and two textile chest attachment loop for ladder climbing.

Special features: Dual florescent colour scheme of High-strength Webbing to differentiate shoulder & thigh straps.

**Sit Strap**: Ideally positioned sit-strap for extended comfort.

Materials: Fray-proof dope-dyed polyester webbing, metal buckles of high-strength alloy steel.

Metal Parts: D-ring & Metal buckles are high strength alloy steel.

**Breaking strength** – 23 kN (Minimum)

**Stitching**: High-strength polyester twist thread, computerized stitching.

**Size adjustment:** chest and thighs straps.

Fall Indicator: In-built Fall Indicator to facilitate easy inspection in case a fall has occurred ever.

Standard: IS 3521(Part-1), EN 361, ISI & CE Mark

Lanyard:

Double lanyard Twisted Polyamide Ropes two end are attached with two Scaffold Hooks and another end incorporated

with dorsal D-Ring of Full Body Harness (FBH).

Total Length: 1.8 mtr.

**Material:** Twisted Polyamide/polyester Rope. **Hooks:** Forged high strength alloy steel. **Breaking strength:** – 23 kN (Minimum)

Stitching: High Strength polyester thread, computerized zigzag stitching instead of splicing.

Standard: IS 3521(Part-2), EN 354, EN 362, ISI & CE Mark