

## **MODEL: SMART-1**

### **Harness:**

**Anchor point:** One dorsal D-ring for fall arrest and two textile chest attachment loops for ladder climbing.

**Special features:** Built-in dual colour webbing for easy orientation.

**Sit Strap :** Ideally positioned sit-strap for extended comfort.

**Materials:** Fray-proof dope-dyed polyester webbing.

**Metal Parts :** D-ring & Metal buckles are high strength alloy steel.

**Stitching :** High-strength polyester twist thread, computerized stitching.

**Adjustability:** Chest and Thighs Straps.

**Breaking strength:** – 23 kN (Minimum)

**Type:** A & L

**Fall Indicator :** In-built Fall Indicator to facilitate easy inspection in case a fall has occurred ever.

**Standard :** IS 3521(Part-1) ISI Mark

### **Lanyard:**

**Description :** Twisted Polyamide Rope Double lanyard with two Scaffold Hooks. Rope Lanyard incorporated with dorsal D-Ring of

Full Body Harness (FBH).

**Total Length:** 1.8 mtr.

**Material:** Twisted Polyamide Ropes, hooks are Forged high strength alloy steel.

**Breaking strength:** – 23 kN (Minimum)

**Stitching:** High Strength polyester thread, computerized zigzag stitching instead of splicing.

**Standard:** IS 3521(Part-2) ISI Mark